




Complete Specification Sheet

RGBW Outdoor

RGBW (Outdoor)

Color Changing Rubber Coated Linear LED



Specifications

Category	Linear LED
Series	Specialty
Environment	RGBW (Outdoor)
Diode	5050
CRI	90+ (White)
CCT Options	3000K
Input Voltage	24V DC
Width	0.47in (12mm)
Height	0.08in (2.2mm)
Cut Intervals	2.46" (62.5mm) , 3.94in (100.0mm)
Beam Angle	120°
Lumens per Foot	160-298 lm/ft
Lumens per Watt	43 lm/W
Life Expectancy	50,000 Hour Life Expectancy
Operating Temp.	-13°F (-25°C) to 140°F (60°C)
Dimming Options	RF, Bluetooth, DMX 512

Features

- Dimmable
- 50,000 Hour Life Expectancy
- UL-Listed for Indoor Use
- 3M™ Industrial Adhesive Backing
- Constant Current
- For Use with Electronic Power Supplies
- IP67 Silicone Jacket


Description

RGBW-1 is our most luminous RGBW tape, delivering over 7 watts per foot, making it suitable for a wide range of applications.





RGBW-2 is our most popular RGBW. With high brightness and power feeds up to 25ft apart, it offers a near perfect balance of light level and run length.

Dimensions

RGBW-1



RGBW-2



Kelvix reserves the right to update the product specifications at any time. To maintain warranty, field modifications must follow approved Kelvix installation instruction.

Conforms to ANSI/UL Standard 2108
Certified to CAN/CSA Standard C22.2 No. 250.2

Fixture Type _____

Project Name _____

Location _____




Product Code Builder

RGBW Outdoor

Product Code Builder

Example: RGBW-1-WR-24V



POWER CHART

	Watts	
	RGBW-1	RGBW-2
1 ft	8.1	5.0
2 ft	14.9	9.0
3 ft	21.6	12.9
4 ft	28.3	16.8
5 ft	34.9	20.6
6 ft	41.6	24.4
7 ft	48.2	28.1
8 ft	54.7	31.7
9 ft	61.3	35.3
10 ft	67.8	38.8
11 ft	74.3	42.2
12 ft	80.7	45.6
13 ft	87.1	48.9
14 ft	93.5	52.2
15 ft	-	55.4
16 ft	-	58.6
17 ft	-	61.6
18 ft	-	64.7
19 ft	-	67.7
20 ft	-	70.5
21 ft	-	73.4
22 ft	-	76.1
23 ft	-	78.9
24 ft	-	81.5
25 ft	-	84.1

	RGBW-1	RGBW-2
Wattage (per ft)	7.2	3.9
Max Run Length (ft)	14	25
Lumens (per ft)	298	160
Efficacy (lm/W)	41	41
Cut Intervals	2.46" (62.5 mm)	3.94" (100.0 mm)
Tape Width	0.47" (12 mm)	0.47" (12 mm)

Kelvix reserves the right to update the product specifications at any time. To maintain warranty, field modifications must follow approved Kelvix installation instruction.
 Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.2

Fixture Type _____
 Project Name _____
 Location _____