






# ZACH 409

LINEAR EASY-SPEC™



### KELVIN COLOR TEMPERATURE SCALE



Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### FEATURES

- 100 to 1000 Lumens per Foot
- Field Replaceable Light Source
- 50,000 Hour Lamp Life
- Dimmable to 1%
- Anodized Finish
- Adjustable-Length Power Feed Included

### SPECIFICATIONS

|                 |                           |
|-----------------|---------------------------|
| Input Voltage   | 24V DC / Constant Voltage |
| CRI             | 90+                       |
| Dimming Options | PWM, Triac, 0-10V         |
| Temp Range      | -40°F to 149°F            |
| Channel Height  | 13mm (1/2")               |
| Channel Width   | 18mm (11/16")             |

### PART NUMBER BUILDER

Example:

**409-I-36-DV-35K-WH-CP-SV-ULV**

| Model      | Setting    | Length<br>(Unlimited) <sup>1</sup> | Output  | CCT  | Lens  | Mounting Method     | Finish  | Power Supply                              |
|------------|------------|------------------------------------|---|--|---|---------------------|---|---|
| <b>409</b> | <b>I</b>   |                                    |   |  |   | <b>CP</b>           | <b>SV</b>   | <b>ULV</b>                                |
| 409        | I - Indoor | Inches                             | DL - 200+lm/ft<br>DK - 400+lm/ft<br>DV - 700+lm/ft<br>VT - 1000+lm/ft<br>RGBW-2<br>RGBW-3 | 24K - 2400 Kelvin<br>27K - 2700 Kelvin<br>30K - 3000 Kelvin<br>35K - 3500 Kelvin<br>40K - 4000 Kelvin<br>50K - 5000 Kelvin | NA - None<br>WH - White<br>SWH - Seamless White<br><i>(SWH for direct view applications only)</i> | CP - Mounting Clips | SV - Silver<br><i>(Custom Finishes Available)</i> | ULV - Universal Power Supply <sup>2</sup> |

<sup>1</sup>Light Source is installed in field allowing for unlimited run lengths  
<sup>2</sup>120V = Forward Phase Dimming | 120/277 = 0-10V Dimming

For use with c us Light Source

Certified to CAN/CSA Standard C22.2 No. 250.0

