



H400-UV-WR-24V


400nm BLACKLIGHT | RUBBERCOATED

LINEAR LED LIGHTING

Fixture Type: _____

Project: _____

Location: _____




PRODUCT FEATURES

- Dimmable
- 50,000 hour life
- 5-year warranty
- UL-listed for indoor and outdoor use
- 3M™ industrial adhesive backing
- For use with 24V power supplies

SPECIFICATIONS

Model	H400-UV-WR-24V (Indoor/Outdoor)
Input Voltage	24V DC / Constant Voltage
Watts per Foot	2.3W/ft @ Maximum Run Length
Beam Spread	120°
Max Run Length	Unlimited, power every 30ft
Production Intervals	3.938" (100mm)
End Cap Dimensions	0.563" (15mm) × 0.375" (9mm)
Tape Dimensions	0.5" (13mm) × 0.25" (6mm)
Diode	5050
Dimming Options	PWM, Triac, 0-10V, DMX, Hi-Lume
Temp Range	-40°F (-40°C) to 149°F (65°C)
Rating	IP67

NANOMETER LIGHT SPECTRUM



TOTAL WATTAGE USED AT EACH LENGTH

1ft	2ft	3ft	4ft	5ft	6ft	7ft	8ft	9ft	10ft	11ft	12ft	13ft	14ft	15ft
5.1	8.9	13	16.8	20.6	23.9	27.1	30.6	33.8	37.5	40.1	42.6	45.2	47.5	50.1
16ft	17ft	18ft	19ft	20ft	21ft	22ft	23ft	24ft	25ft	26ft	27ft	28ft	29ft	30ft
51.6	53.2	54.9	56.1	57.8	59.5	61.7	62.6	64.9	65.9	67.3	67.6	68.2	68.7	68.8

Conforms to ANSI/UL Standard 2108
 Certified to CAN/CSA Standard C22.2 No. 250.0

